

Replace the Motor Rotor Assembly - Classic

Entire document: 3 pages

THIS DOCUMENT CONTAINS GENERAL INSTRUCTION FOR SERVICING STENNER PRODUCTS. PLEASE BE SURE TO READ <u>ALL</u> SAFETY INFORMATION.

- NOTICE: Indicates special instructions or general mandatory action.
- **NOTICE:** Read all safety hazards before installing or servicing the pump. The pump is designed for installation and service by properly trained personnel.
- **NOTICE:** Use all required personal protective equipment when working on or near a chemical metering pump.
- **NOTICE:** Install the pump so that it is in compliance with all national and local plumbing and electrical codes.
- **NOTICE:** Use the proper product to treat potable water systems, use only chemicals listed or approved for use.
- NOTICE: Install the pump to work in conjunction with pool, spa, well pump, or system controls.





Safety Information - Classic

Page 2 of 3

MARNING Warns about hazards that CAN cause death, serious personal injury, or property damage if ignored.

ELECTRIC SHOCK HAZARD

A WARNING ELECTRIC SHOCK HAZARD:

Pump supplied with grounding power cord and attached plug. To reduce risk of electrical shock, connect only to a properly grounded, grounding type receptacle. Install only on a circuit protected by a ground-fault circuit interrupter (GFCI).

A AVERTISSEMENT RISQUE DE CHOC ELECTRIQUE:

Cette pompe est équipée d'une fiche de mise à terre. Pour réduire le risque de choc électrique, s'assurer que la fiche est bien raccordée à une prise de courant avec une connexion de mise à terre. Installer seulement sur un circuit proteger par un interrupteur proteger par une mise à la terre.

DO NOT alter the power cord or plug end.

DO NOT use receptacle adapters.

DO NOT use pump with a damaged or altered power cord or plug. Contact the factory or an authorized service facility for repair.

CAUTION Warns about hazards that WILL or CAN cause minor personal injury or property damage if ignored.

A CAUTION PLUMBING:

Chemical feed pump installation must always adhere to your local plumbing codes and requirements. Be sure installation does not constitute a cross connection. Check local plumbing codes for guidelines.

- NOTICE: Indicates special instructions or general mandatory action.
- NOTICE: This metering pump is portable and designed to be removable from the plumbing system without damage to the connections.
- NOTICE: This metering pump and its components have been tested for use with the following chemicals: Sodium Hypochlorite (10-15%), Muriatic Acid (20-22% Baume, 31.5% Hcl), and Soda Ash.
- NOTE: Cette a pompe de dosage et ses composants ont été testés pour utilisation avec les produits chimiques suivants; Hypochlorite de Sodium (solution de 10-15%); Acide Muriatique (20-22% Baume, 31.5% Hcl); Cendre de Soude.

⚠ MARNING HAZARDOUS VOLTAGE:

DISCONNECT power cord before removing motor cover for service. **Electrical service by trained personnel only.**

A WARNING EXPLOSION HAZARD:

This pump is not explosion proof. **DO NOT** install or operate in an explosive environment.

A WARNING RISK OF CHEMICAL EXPOSURE:

Potential for chemical burns, fire, explosion, personal injury, or property damage. To reduce risk of exposure, the use of proper personal protective equipment is mandatory.

A WARNING RISK OF FIRE HAZARD:

DO NOT install or operate on any flammable surface.

A WARNING RISK OF CHEMICAL OVERDOSE:

To reduce risk, follow proper installation methods and recommendations. Check your local codes for additional guidelines.

This is the safety alert symbol. When displayed in this manual or on the equipment, look for one of the following signal words alerting you to the potential or personal injury or property damage.

PUMP SUITABLE FOR USE OUTDOORS when installed with a Stenner Rain Roof Part No. MP90000.

Electrical installation should adhere to all national and local codes. Consult a licensed professional for assistance with proper electrical installation.

Removing power from pool/spa recirculation pump must also remove power from pump.

The use of an auxiliary safety device (not supplied), such as a flow switch or sensor, is recommended to prevent feed pump operation in the event of a recirculation pump failure or if flow is not sensed.

Point of chemical injection should be beyond all pumps, filters, and heaters.

Suitable for indoor and outdoor use.


Convient pour usage intérieur et extérieur.






Replace the Motor Rotor Assembly - Classic

Page 3 of 3





A new rotor assembly includes B, D & F.

- 1. Remove and set aside:
 - Two motor housing screws (not shown)
 - · Motor housing A
 - · Plastic fan B (discard old fan)
 - Two coil screws and lock washers C
 - Coil (keep wires connected) E
- 2. Remove and discard the rotor F and two amber bearing brackets D.
- 3. Press the new amber bearing bracket D onto the threaded brass inserts in the back of the gear case G.
- 4. Install the new rotor F by inserting the shaft (helical gear side) onto the amber bearing bracket D.
- 5. Place the coil E (see Correct Coil Orientation) over the rotor F onto the bearing bracket D.
- 6. Snap into place the second bearing bracket onto the rotor.
- 7. Insert two coil screws with lock washers C and tighten.
- 8. Starting at an angle, press fan **B** (with hub side down) onto the rotor shaft.
- 9. Reinstall the two motor housing screws and tighten the self-tapping screws to secure the motor housing A.